Product Data Sheet

Belts · Rolls



KK711Y





VSM ALUMINIUM OXIDE



grinding

Grain type	Aluminium oxide	
Bonding	Full-resin bonded	
Colour	Red-brown	
Backing	Y-Polyester (P36-P180) Y-Cotton (P220-P500)	
Flexibility	Very sturdy	
Production width	1,480 mm (P36-P180) 1,450 mm (P220-P500)	

Materials			Featur	
	STAINLESS STEEL	SUPER- ALLOY	•	
Unalloyed steel	Stainless Steel	Superalloys	Medium pressure	
AI DO	Cu Ni Zn		\Diamond	
Aluminium	Non-ferrous	Wood	Also for wet	

Aluminium oxide abrasive belt for all types of application. Thanks to the very robust polyester backing, KK711Y offers high edge stability when applying low to medium contact pressure. Ideal complement to KK711X, if an even more robust backing is needed.

Grit sizes:1)



Benefits

- > High performance abrasive
- > Universally applicable
- > Long service life
- > Highly resilient
- > Cooling lubricant resistant up to and including P80

VSM · Vereinigte Schmirgelund Maschinen-Fabriken AG

Siegmundstraße 17 · 30165 Hanover · Germany T +49 511 3526 479 · F +49 511 3521 315 sales@vsmabrasives.com · www.vsmabrasives.com









