



KV710X



VSM NON-WOVEN (AO/SIC)




Grain type	Aluminum oxide / Silicon carbide
Bonding	Full-resin bonded
Colour	Coarse = brown (AO) Fine = red (AO) Very fine = blue (AO) Ultra fine = grey (SIC)
Backing	X-Polyester
Production width	39 in

Materials



Features



Surface conditioning material with optimized, open fiber structure, without any inclusions or islands of resin. This non-woven abrasive has significantly reduced clogging even with grinding non-ferrous metals. KV710X ensures a consistent scratch pattern throughout its entire, long service life. The backing is soft and flexible to adapt to the contours of the workpiece

AO = aluminum oxide SIC = silicon carbide

Fineness range:¹⁾



Benefits

- > No clogging or smearing, even with non-ferrous metals
- > Homogeneous, open texture without any inclusions or lumps of resin
- > Low-stretch backing: Comparatively soft and flexible enough to adapt to the contours of the workpiece
- > Consistent scratch pattern
- > Very high stock removal
- > Very long service life
- > Reduced part discoloration

VSM Abrasives Corp.

1012 East Wabash Street · O'Fallon, MO 63366 · USA
 T +1 800 737 0176 · F +1 636 272 6394
 us.info@vsmabrasives.com · www.us.vsmabrasives.com

¹⁾ Further grit sizes upon request. Subject to technical changes.

